

EC-97912-15

990 SLIDING DOOR QUOTE REQUEST & ORDER ENTRY FORM

CUSTOMER NAME \_\_\_\_\_

STREET ADDRESS \_\_\_\_\_

CITY / STATE / ZIP \_\_\_\_\_

JOB NAME \_\_\_\_\_

DATE \_\_\_\_\_

ORDER NO. \_\_\_\_\_

ITEM NO. \_\_\_\_\_

**NOTE: PLEASE CHECK APPROPRIATE BOX OR BOXES UNDER EACH HEADING BELOW**

**ACTUAL UNIT WIDTH** ..... FT. \_\_\_\_\_ IN.

**ACTUAL UNIT HEIGHT** ..... FT. \_\_\_\_\_ IN.

**FINISH** .....  #14     #17     #18     #26

\*PAINT FINISHES - ADD  #28     #29     #40

COLOR/FINISH NUMBER  BW - BONE WHITE\*

#22\*

\*PAINT COLOR \_\_\_\_\_

\*PAINT NUMBER \_\_\_\_\_

**QUANTITY** ..... (NO. OF UNITS)

**GLAZING** .....  1/4"     3/8"     5/8"     1"

**UNIT TYPE** .....  OX     OXO-L

XO     OXO-R

OXXO

**STRUCTURAL REQUIREMENTS** .....  \_\_\_\_\_  
(WIND LOAD IN PSF) (Specify)

**SCREENS** .....  NO

STD.

HEAVY DUTY

**MUNTINS** .....  NO

YES \_\_\_\_\_ FT. \_\_\_\_\_ IN.  
(Ht. = C/L of Pull to Btm. of Sill)

**PERIMETER MEMBERS** .....  NO

SUB-HEAD & SUB-JAMBS

SUB-HEAD ONLY

SUB-JAMBS ONLY

**LOCKING HARDWARE**

1848 LATCH

- 1848 LATCH/EXTRUDED PULLS
- 1848 LATCH/FLUSH PULLS
- 5/8" O.S. CYLINDER
- SUBST. THUMBTURN
- SUBST. STAINLESS STEEL LOCK & STRIKE

MS HOOKBOLT

- MS HOOKBOLT/EXTRUDED PULLS  
WITH (2) CYLINDERS
- MS HOOKBOLT/FLUSH PULLS  
WITH (2) CYLINDERS
- SUBST. THUMBTURN ON MS

HARDWARE

STD.

LOCATION

SPECIAL HEIGHT \_\_\_\_\_ FT. \_\_\_\_\_ IN.  
(Ht. = C/L of Pull to Btm. of Sill)

**STAINLESS STEEL ROLLERS**.....  YES     NO

**ADDITIONAL INFORMATION OR SKETCH:**

Laws and building and safety codes governing the design and use of glazed entrance, window, and curtain wall products vary widely. Kawneer does not control the selection of product configurations, operating hardware, or glazing materials, and assumes no responsibility therefor.

Kawneer reserves the right to change configuration without prior notice when deemed necessary for product improvement.  
© Kawneer Company, Inc., 2012

GLASS SIZES FOR 990 DOORS	UNIT TYPE	UNITS WITH 1848 LATCH	UNITS WITH M.S. HOOKBOLT
*STANDARD INTERLOCKS	OX or XO	$\frac{\text{ACTUAL FRAME WIDTH} - 4\frac{1}{4}"}{2} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 4\frac{3}{4}"}{2} = \text{G.W.}$
	OXO	$\frac{\text{ACTUAL FRAME WIDTH} - 5\frac{1}{8}"}{3} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 5\frac{5}{8}"}{3} = \text{G.W.}$
	OXXO	$\frac{\text{ACTUAL FRAME WIDTH} - 6\frac{7}{8}"}{4} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 7\frac{3}{8}"}{4} = \text{G.W.}$
*MEDIUM INTERLOCKS	OX or XO	$\frac{\text{ACTUAL FRAME WIDTH} - 4\frac{1}{4}"}{2} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 4\frac{3}{4}"}{2} = \text{G.W.}$
	OXO	$\frac{\text{ACTUAL FRAME WIDTH} - 5\frac{1}{8}"}{3} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 5\frac{5}{8}"}{3} = \text{G.W.}$
	OXXO	$\frac{\text{ACTUAL FRAME WIDTH} - 7\frac{3}{8}"}{4} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 7\frac{7}{8}"}{4} = \text{G.W.}$
*MAXIMUM INTERLOCKS	OX or XO	$\frac{\text{ACTUAL FRAME WIDTH} - 5"}{2} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 5\frac{1}{2}"}{2} = \text{G.W.}$
	OXO	$\frac{\text{ACTUAL FRAME WIDTH} - 6\frac{5}{8}"}{3} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 7\frac{1}{8}"}{3} = \text{G.W.}$
	OXXO	$\frac{\text{ACTUAL FRAME WIDTH} - 8\frac{7}{8}"}{4} = \text{G.W.}$	$\frac{\text{ACTUAL FRAME WIDTH} - 9\frac{3}{8}"}{4} = \text{G.W.}$
GLASS HEIGHT	ALL	FRAME HEIGHT - 4-9/16"	

\*FORMULAS ARE FOR CALCULATING GLASS WIDTH ONLY, AND IS BASED ON EQUAL SIZE LIGHT OPENINGS.

Laws and building and safety codes governing the design and use of glazed entrance, window, and curtain wall products vary widely. Kawneer does not control the selection of product configurations, operating hardware, or glazing materials, and assumes no responsibility therefor.

Kawneer reserves the right to change configuration without prior notice when deemed necessary for product improvement.  
© Kawneer Company, Inc., 2012