




| Product | 1010 Sliding Mall Front | 1010C Sliding Mall Front | 1040 Sliding Mall Front | |
|----------------------------|---|--|---|--|
| Catalog Section | Sliding Doors | Sliding Doors | Sliding Doors | |
| Typical Detail |  |  |  | |
| Sightline | 1", 1-3/4", 3-7/16", 5-1/8" | 1-3/4", 2-5/16", 2-15/16" | 2-1/8", 4" | |
| Depth | Varies by # of panels | Varies by # of panels | 1-3/4" | |
| Applications | Interior | Interior | Interior or Exterior | |
| Infill Options | Up to 1" | 3/16" & 1/4" | 1/4" & 1" | |
| Cross Rails/Muntins | Yes | Yes | Yes | |
| Product Description | The 1010 sliding mall front is a floor supported, multi-track (surface or recessed), sliding door offering parallel in-line stacking. The 1010 sliding mall front is intended to be used primarily as an interior unit. It may be used as an exterior unit when optimum weathering performance is not required. | The 1010C sliding mall front is a floor supported, multi-track (surface or recessed), sliding door offering parallel in-line stacking. The 1010C sliding mall front is intended to be used primarily as an interior unit. It may be used as an exterior unit when optimum weathering performance is not required. It accepts a swinging entrance door within the sliding panels. | The 1040 sliding mall front is a floor supported, single track (surface or recessed), sliding door offering three separate stacking options (Parallel staggered, parallel even and 90° stacking). The 1040 sliding mall front is intended to be used primarily as an interior unit. It may be used as an exterior unit when optimum weathering performance is not required. | |
| Hurricane Resistant Tested | — | — | — | |
| Performance Class/Rating | — | — | — | |
| Performance Test Standards | — | — | — | |

Laws and building and safety codes governing the design and use of glazed entrance, window, and curtain wall products vary widely. Kawneer does not control the selection of product configurations, operating hardware, or glazing materials, and assumes no responsibility therefor.

Kawneer reserves the right to change configuration without prior notice when deemed necessary for product improvement.
© Kawneer Company, Inc., 2014